




VESTIL ERGONOMIC SOLUTIONS



Lift and Tilt Equipment

Electric Hydraulic Scissor Lift Tables

Used by all types of manufacturing and warehouse facilities. Safety features include: electric toe guard to protect pinch points during lowering of the table, brass velocity fuse to maintain platform height regardless of hydraulic pressure, 24V AC push-button hand control, maintenance prop, and upper travel limit switch to stop table at maximum height reducing motor wear. 2HP, 460V, 3 phase, 60 Hz totally enclosed motor standard, other voltages available. 3000 psi hydraulic component rating. Additional sizes and capacities available.



MODEL NUMBER	PLATFORM SIZE (W x L)	SERVICE RANGE	CAPACITY (POUNDS)	NET WT. (POUNDS)
EHLT-2448-3-43	24" x 48"	7" to 43"	3,000	700
EHLT-4848-3-43	48" x 48"	7" to 43"	3,000	825
EHLT-2448-4-43	24" x 48"	7" to 43"	4,000	775
EHLT-4848-4-43	48" x 48"	7" to 43"	4,000	910

Ground Lift Scissor Tables

- Ideal for Pallet Truck Loading
- Capacity 2,000 lbs.
- Service Range 1/2" to 36"
- Foot Control Standard
- 2HP, 208-230/460V, 3-phase, 60 Hz
- Remote Power Unit can be Located up to 8 ft. Away
- Additional Sizes and Capacities Available.



MODEL NUMBER	PLATFORM SIZE (W x L)	OVERALL SIZE (W x L x H)	NET WT. (POUNDS)
EHLTG-4450-2-36	44" x 50"	67" x 56" x 8½"	1620
EHLTG-5250-2-36	52" x 50"	75" x 56" x 8½"	1690

DC Powered Elevating Cart

- Designed to Bring Materials to an Ergonomic Height to Reduce Bending
- DC Powered Lift with Battery and On-Board Charger
- Raise and Lower Platform with a Push Button Control
- Capacity 1,000 lbs.
- (4) Polyurethane Casters



model CART-1000-DC model CART-DS-1000

MODEL NUMBER	PLATFORM SIZE (W x L)	SERVICE RANGE	NET WT. (POUNDS)
CART-1000-DC	20½" x 39¾"	17½" to 37½"	419
CART-DS-1000	20" x 33"	14" to 40"	370

Hydraulic Elevating Carts

- Minimize Worker Bending and Lifting
- Two Speed Foot Pump Operation (except CART-400)
- Foot Pump Includes a Soft-Lowering Down Valve
- Chrome Platform (except CART-2000)
- Internal Hydraulic Velocity Fuse in Each Cylinder
- (4) Polyurethane Casters (2 swivel with brakes and 2 rigid)



CART-400

CART-750-TS
CART-1000-TS

CART-800-D-TS

CART-1000-LD

CART-1500-D-TS

MODEL NUMBER	DESCRIPTION	PLATFORM SIZE (W x L)	CAPACITY (POUNDS)	SERVICE RANGE	FOOT PUMP SPEED	NET WT. (POUNDS)
CART-400	SINGLE SCISSOR	17½" x 27½"	400	8¾" to 29"	SINGLE	108
CART-800-D-TS	DOUBLE SCISSOR	20" x 35½"	800	15½" to 50¾"	TWO	330
CART-1000-TS	SINGLE SCISSOR	19¾" x 32½"	1,000	15½" to 35½"	TWO	205
CART-1000-LD	SINGLE SCISSOR	32" x 68"	1,000	15" to 39"	TWO	340
CART-1500-D-TS	DOUBLE SCISSOR	24" x 47½"	1,500	19½" to 68½"	TWO	552
CART-1750	SINGLE SCISSOR	20" x 39½"	1,750	16" to 39"	SINGLE	288
CART-2000	SINGLE SCISSOR	20" x 40"	2,000	15" to 39"	TWO	288



CART-2000

Single Scissor Lift & Tilt Tables

Designed to position containers within easy reach of assembly line workers and machine operators. This unique design reduces fatigue by minimizing repetitive bending and stretching required to obtain components from containers. Platform includes a 12" high lip on tilt side. Level height of the unit is 8". Capacity is 4,000 lbs. A selector pedal allows the operator to lift while tilting or tilt then lift. 2HP AC power unit with hand pendant control is standard 208-230/460V, 3PH.



MODEL NUMBER	PLATFORM SIZE (W x L)	MAXIMUM TILT	POWER UNIT	NET WT. (POUNDS)
UNI-2448-4	24" x 48"	40°	EXTERNAL	631
UNI-3648-4	36" x 48"	40°	INTERNAL	676
UNI-4848-4	48" x 48"	40°	INTERNAL	792
UNI-5448-4	54" x 48"	40°	INTERNAL	870

Portable Uni-Tilts

Now you can transport your tilter from workstation to workstation quickly and easily with a fork truck. Usable fork pockets are 7-1/2"W x 2-1/2"H. Capacity is 4,000 lbs. Platform includes a 12" high lip on tilt side. Level height is 12". A selector pedal allows the operator to lift while tilting or tilt then lift. Features the same standard features as our original Single Scissor Lift and Tilt Table above.



MODEL NUMBER	PLATFORM SIZE (W x L)	MAXIMUM TILT	POWER UNIT	NET WT. (POUNDS)
UNI-P-4848-4	48" x 48"	40°	INTERNAL	1197
UNI-P-5448-4	54" x 48"	40°	INTERNAL	1241

Lift and Tilt Carts with Sequence Select

- Operated with a Foot Actuated Hydraulic Cylinder
- As the Table is Raised, it Simultaneously Tilts
- Tilt Angle at Full Elevation is 45°
- Built-In Retaining Lip keeps Containers in Place
- (4) Polyurethane Casters (2 swivel with brakes and 2 rigid)
- *Service Range Figured with Platform Level



MODEL NUMBER	PLATFORM SIZE (W x L)	CAPACITY (POUNDS)	*SERVICE RANGE	NET WT. (POUNDS)
CART-400-LT	19½" x 30"	400	13" to 31"	200
CART-600-LT	24" x 36"	600	14" to 35"	300