

Vertical Clamps

IPNM10





The IPNM10 vertical lifting clamp is used for the lifting, turning, moving or vertical transfer of sheet, plates, or fabrications from horizontal to vertical and down to horizontal (180°) as needed without marring the surface of the material. Materials such as aluminum, stainless steel, painted materials, aircraft skins, composite material, glass, plastic, etc., can be lifted without marring. The hinged hoisting eye allows for the clamp to place and lift the load from any direction, or with a multiple leg sling without side-loading the clamp.

Will NOT mar, or scratch the material surface.

For use in almost all sectors of industry where during the lift or transfer, no damage to the material is permitted.

- Available in capacities of .5 and 1 metric tons.
- Wide variety of jaw openings available: 0 to 3/4".
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- Company name (IP), logo, Working Load Limit and jaw opening permanently stamped on body.
- Each product is individually serialized, with the serial number and Proof Load test date stamped on body. Serial number is included on the test certificate with maintenance and warranty logbook.
- Full 180° turning range for material transfer, turning or moving.
- Lock open, lock closed ability with latch for pretension on material and then release of material.
- Minimum WLL of 10% of Maximum WLL.
- Maintenance replacement kits are available.
- Manufactured by a ISO 9001 facility.



Model IPNM10

Model	Working Load Limit (t)*	IPNM10 Stock No.	Weight Each (lbs.)	Dimensions (in.)								
				Jaw A	B	C	D	E	F	G	H	K
IPNM10	0.5	2703276	6	0 - .38	1.73	5.05	8.16	1.19	4.53	1.61	1.11	0.39
IPNM10	1	2703277	9	0 - .75	1.75	5.47	8.46	1.19	4.47	1.63	1.50	0.39

* Ultimate load is 5 times the Working Load Limit.

Other Non-Marring Clamps



Vertical Non-Marring Lifting Clamp with Protection Cap (IPNM/P).
2 Types: WLL 0.5 ton and 1 ton



Horizontal Non-Marring Lifting Clamp (IPHNM).
2 Types: WLL 0.5 and 1 ton



Vertical Non-Marring Screw Clamp (IPSNM).
2 Types: WLL 0.1 and 0.25 ton