



Fixed Beam Anchor 2108406

- Anchor is easily installed by sliding the adjustable hook-end down to the flange and securing a pin
- Easily adjust to exactly where you want it in any orientation or direction
- Fits 1-1/2" thick flange, 2-1/2" to 12" wide
- 5,000 lbs. minimum strength in any direction



Tie-Off Adaptor 1003000

- Pass-through design makes attaching to anchorage quick and easy
- 1-3/4" polyester strength member (5,000 lb. Min. tensile strength)
- 3" wide polyester wear pad for added abrasion resistance and product longevity
- 3 ft. in length, other lengths available
- Coated steel hardware for corrosion resistance and strength



Sayflin Horizontal Lifeline System 7600502

- Sayflin™ system is a complete kit coming in its own carrying bag that is easily installed with no special tools or equipment
- System is lightweight (12 lbs.) and extremely portable allowing you to move it and reuse it over and over again
- Complete with kernmantle rope lifeline assembly with a tensioning device for ease-of-use
- Two tie-off adaptors are included to anchor the system to a structure
- System length = 20 ft. (30, 40, 50, 60, 70, 80, 90 and 100 ft. systems are also available)



Ultra-Lok® Self Retracting Lifeline 3504430

- Stainless steel working components for corrosion resistance
- 30 ft. 3/16" galvanized steel wire rope for durability
- Reserve lifeline retention system for added safety
- Self-locking swivel snap hook with impact indicator
- Swiveling anchorage loop to prevent twisting of lifeline



Ultra-Lok® Self Retracting Lifeline - 20 ft. web 3103208

- Stainless steel working components for corrosion resistance
- 20 ft. one-inch nylon web lifeline for reduced weight
- Reserve lifeline retention system for added safety
- Self-locking swivel snap hook with impact indicator
- Swiveling anchorage loop to prevent twisting of lifeline



AD111A Rebel® AD111A

- The industry's lightest and most compact 11 foot SRL
- Lightweight and compact aluminum housing construction weighing only 2.8 lbs.
- Best lifeline length-to-weight ratio in the industry
- Unique super strength thin webbing for total security and added length in a compact SRL
- Unique speed sensing brake reduces clearance requirements and limits fall arrest forces to 900 lbs. or less
- Designed for smooth consistent operation
- AJ565A snap hook on lifeline, AJ514A carabiner on housing
- Two year warranty, no recertification necessary



All above items meet or exceed all applicable industry standards including OSHA, ANSI and the stringent ANSI Z359